

Material: Nylon PA Poliamida
Grado de Retardante a Flama: UL940V0
Metal: Latón Niquelado



Bloques de Distribución PowerBlock

Código MAZ	04-40-033	04-40-034	04-40-035	04-40-036	04-40-037	04-40-038
Código TM	TMK-80	TMK-125	TMK-160	TMK-250	TMK-400	TMK-500
Corriente	80 Amp	125 Amp	160 Amp	250 Amp	400 Amp	500 Amp
Voltaje	690V IEC	690V IEC	690V IEC	690V IEC	690V IEC	690V IEC
Entradas	1 Entrada 6mm ² a 16mm ²	1 Entrada 10mm ² a 35mm ²	1 Entrada 10mm ² a 70mm ²	1 Entrada 35mm ² a 120mm ²	1 Entrada 95mm ² a 185mm ²	*1 Entrada 4x15.5x0.8mm
Salidas	4 Salidas 2.5mm ² a 6mm ²	7 Salidas 2.5mm ² a 16mm ²	7 Salidas 2.5mm ² a 16mm ²	2 Salidas 6mm ² a 35mm ²	2 Salidas 6mm ² a 35mm ²	2 Salidas 6mm ² a 35mm ²
	2 Salidas 2.5mm ² a 16mm ²			5 Salidas 2.5mm ² a 16mm ²	5 Salidas 2.5mm ² a 16mm ²	5 Salidas 2.5mm ² a 16mm ²
				4 Salidas 2.5mm ² a 10mm ²	4 Salidas 2.5mm ² a 10mm ²	4 Salidas 2.5mm ² a 10mm ²
Dimensiones	28x65x47mm	28x74x48mm		47x95x50mm		
* Entrada de pletina 4x15.5x0.8mm						