









Los datos técnicos

Tipo de	Ración (A)	Carga (VA)	La clase de precisión
DM-20	15/5	-	1,0
	20/5	-	1,0
	25/5	-	1,0
	30/5	-	1,0
	40/5	-	1,0
	50/5	1	1,0
	60/5	1	1,0
	75/5	1,5	1,0
	80/5	1,5	1,0
	100/5	2,5	1,0
	125/5	2,5	0,5
	150/5	3	0,5
	200/5	5	0,5
	250/5	5	0,5
300/5	5	0,5	
Frecuencia nominal			50/60Hz
Nominal Tensión de prueba			3kV AC (1 min)
Corriente térmica calificada de corto plazo (Ith)			60In
Corriente dinámica nominal (Idyn)			2.5Ith
Voltaje nominal (Um)			0.72kV AC
Sobrecarga continua (Id)			1.2In
Temperatura de funcionamiento			-10 °C ~ 50 °C
Carcasa de clase de autoextinción			VO
Factor de seguridad FS			FS 5
Secundaria actual			5A/1A

Current Transformers	Ratio	1.0级	0.5级	0.5S级	0.2级	0.2S级	匝数	Outline and installation dimensions
 <p>DM-20</p>	50/5						1	
	60/5						1	
	75/5	1.5					1	
	100/5	1.5	1				1	
	150/5	2.5	1.5				1	
	200/5	2.5	2.5				1	
	300/5	5	5				1	
 <p>DX-20</p>	50/5	1.5					1	
	75/5	2.5					1	
	100/5	5					1	
	150/5	5	2.5				1	
	200/5	5	5				1	
	250/5	5	5	2.5	2.5		1	
	300/5	5	5	2.5	2.5		1	
 <p>DX-30</p>	30/5	0.5					1	
	40/5	1					1	
	50/5	1					1	
	75/5	1.5					1	
	100/5	1.5					1	
	150/5	2.5					1	
	200/5	5	1.5				1	
	250/5	5	2.5				1	
	300/5	5	2.5				1	
 <p>DX-40</p>	150/5	2.5	2.5				1	
	200/5	5	2.5				1	
	250/5	5	5	2.5			1	
	300/5	5	5	5			1	
	400/5	5	5	5			1	
	500/5	5	5	5			1	
	600/5	10	5	5			1	