


## SPC 06-N02, 6 mm O.D Tubing, 1/4 NPT Thread Male Straight Stainless Steel Push in Fitting

Pneuflex SPC 06-N02 male straight stainless steel push in fitting (stainless steel push to connect fitting) connects a female 1/4 NPT thread to a 6 mm O.D nylon, polyurethane, polyethylene or Teflon tubing in same direction. 6 mm tubing x 1/4 NPT male straight stainless steel push in fitting is made of 316 stainless steel for corrosion resistance, FKM sealing material for chemical-resistance. 6 mm O.D tubing, 1/4 NPT thread male straight stainless steel push in fitting is suitable for use with air, water, oil and steam in high temperature and wash-down applications. External tightening with a flat wrench; internal tightening with a hexagon wrench.



**Part #:** SPC 06-N02  
**Push-in Tubing O.D:** 6mm  
**Thread Size:** 1/4 NPT  
**Fluid Admitted:** Air, Vacuum, Water\*, Steam, Oil  
**Thread Material:** 316 Stainless Steel  
**Seal:** FKM (Viton)  
**Working Pressure:** 0 — 2.0MPa | 0 — 290psi  
**Proof Pressure:** 3.0MPa | 435psi  
**Negative Pressure:** -100Kpa | -29.5 In Hg  
**Working Temperature:** -20—150°C | -4—302°F  
**MOQ:** 50PCS

Dimensions of SPC 06-N02, 6 mm O.D Tubing, 1/4 NPT Thread Male Connector, Male Straight Stainless Steel Push in Fitting



Part No.	TUBE	R	L	L1	CH
SPC 06-N02	6mm	1/4 NPT	23mm	11mm	14mm