


SPC 08-N02, 8 mm O.D Tubing, 1/4 NPT Thread Male Straight Stainless Steel Push in Fitting

Pneuflex SPC 08-N02 male straight stainless steel push in fitting (stainless steel push to connect fitting) connects a female 1/4 NPT thread to a 8 mm O.D nylon, polyurethane, polyethylene or Teflon tubing in same direction. 8 mm tubing x 1/4 NPT male straight stainless steel push in fitting is made of 316 stainless steel for corrosion resistance, FKM sealing material for chemical-resistance. 8 mm O.D tubing, 1/4 NPT thread male straight stainless steel push in fitting is suitable for use with air, water, oil and steam in high temperature and wash-down applications. External tightening with a flat wrench; internal tightening with a hexagon wrench.



Part #: SPC 08-N02
Push-in Tubing O.D: 8mm
Thread Size: 1/4 NPT
Fluid Admitted: Air, Vacuum, Water*, Steam, Oil
Thread Material: 316 Stainless Steel
Seal: FKM (Viton)
Working Pressure: 0 — 2.0MPa | 0 — 290psi
Proof Pressure: 3.0MPa | 435psi
Negative Pressure: -100Kpa | -29.5 In Hg
Working Temperature: -20—150°C | -4—302°F
MOQ: 50PCS

Dimensions of SPC 08-N02, 8 mm O.D Tubing, 1/4 NPT Thread Male Connector, Male Straight Stainless Steel Push in Fitting



Part No.	TUBE	R	L	L1	CH
SPC 08-N02	8mm	1/4 NPT	24mm	11mm	14mm